

high performance PD accessories

PDCAL PLUS Hi Energy Partial Discharge Calibrator



PDCAL PLUS is designed for field application thanks to its internal battery supply.

PDCAL PLUS extended pulse version is able to perform up to 800 pC pulse.

PDCAL PLUS calibrator consist of a microprocessor controlled pulse generator allowing the user to select several output pulse-with through simple up-down pushbuttons operation.

Thanks to on board photo coupler PDCAL PLUS output pulse can be synchronized with the actual line frequency through external surrounding electrical light source.

PDCAL PLUS have excellent pulse-with stability; scale calibration factors are permanently stored inside its flash memory.



Specifications

Programmable Pulse Out: 50 pC, 80 pC, 100 to 800 pC @ 100 pC step

Pulse Accuracy: IEC 60270 compliant

Adjustable pulse repetition rate: 0.5 – 1 – 2 – 4 pulse per cycle

Internal supply: single 9 V battery Room light synchronization feature

Pulse Output connector: Standard BNC type

Injection capacitance < 200 pF



www.altanova-group.com



TECHIMP - ALTANOVA GROUP Via Toscana 11, 40069 Zola Predosa (Bo) - Italy T +39 051 199 86 050 Email sales@altanova-group.com



ISA - ALTANOVA GROUP Via Prati Bassi 22, 21020 Taino (Va) - Italy T +39 0331 95 60 81 Email isa@altanova-group.com



intelliSAW - ALTANOVA GROUP 100 Burtt Rd Andover, MA 01810, USA T +1 978-409-1534 Email contact@intellisaw.com